



METHOD AND APPARATUS FOR CONTROLLING AND APPLYING RESOURCE OF

IDLE SCREEN ON MOBILE

Technical Field

5 The present invention relates to a mobile communication terminal and method of driving the same, and an idle screen service system and method using the same. More particularly, the present invention relates to a mobile communication terminal, which has an idle screen function ~~of~~ providing idle screen information that is set in a terminal and an Internet service by a user to a user mobile communication terminal, and displaying the provided idle screen information, and provides a method of displaying an idle screen, a method of driving the same, and an idle screen service system and method using the same.

15

Background Art

With the development of a ~~wireless~~ Internet service, a user-oriented information service has been provided, which has come ~~comes~~ to popularize a wireless Internet. Generally, in a wireless Internet service system, ~~any~~ information is transmitted to a user in the form of a SMS (Short Message Service) message. Information received as the SMS message is stored in a mobile communication terminal as a simple message. In this case, multimedia information such as financial information and entertainment banners are not consistently shown.

25

In a current wireless Internet service system, the use of

multimedia information has increased due to the adoption of a color screens ~~of~~ on a mobile communication terminal, the higher ~~specification~~ quality of the portable mobile communication devices, the improvement of wireless Internet speed, and the like.

Further, a conventional information transmission method is accomplished through SMS service for specialized information that is not information set by a user. Thus, there is a disadvantage in that a user cannot set and use a variety of financial information and entertainment information.

Moreover, in the conventional information transmission service using SMS service, the amount of data that can be transmitted at once is limited. Thus, there is a problem in that ~~information of~~ an audio or video type information cannot be provided to a user.

Furthermore, the conventional information transmission service using SMS simply transmits information. Thus, there is a problem in that it does not provide an interactive function with a user who accesses a relevant wireless Internet web site through a hyperlink function.

Also, the conventional information providing method has problems in that a user can obtain information only through access using an Internet access application or browser built in a portable mobile communication device, and specialized information for every user cannot be provided.

In order to solve the above-described conventional problems,

there was proposed Korean Patent Registration No.391291, the applicant of which is the same as that of this application.

Korean Patent Registration No.391291 discloses that contents information to be provided to a mobile communication terminal are converted into a message format which is suitable for transmission through a mobile communication network, and the converted sliding message is transmitted to the mobile communication terminal, so that a user can confirm the contents information. However, Korean Patent Registration No.391291 does not disclose concrete embodiments of a method of configuring templates in which contents information is displayed and a method of providing the information. In this connection, the present invention proposes a more detailed method of configuring templates and a method of providing information.

Technical Problem

Accordingly, the present invention has been made in view of the above problems occurring in the prior art, and it is an object of the present invention to provide a mobile communication terminal having an idle screen control function in which idle screen information for user information is received/stored, and the stored idle screen information is displayed.

Another object of the present invention is to provide a method of driving a mobile communication terminal having the idle screen control function, and an information providing

method.

Still another object of the present invention is to provide a method of providing information requested by a user using a mobile communication network for providing relevant information to a mobile communication terminal according to information set by a user who wants to receive the information through the mobile communication terminal or an Internet accessible PC, and an idle screen service method.

Further another object of the present invention is to provide a system for performing the idle screen service method using the mobile communication network.

Further another object of the present invention is to provide a method of displaying resources stored in a portable mobile communication device, which are frequently used by a user, on an idle screen in the form of an icon so that the user can easily use the resources.

Further another object of the present invention is to provide a method of operating and managing a channel so that the transfer of information can be controlled and managed in an efficient manner.

Technical Solution

To achieve the above ~~object(s)~~ objects, according to the present invention, there is provided an apparatus for controlling and operating resources of an idle screen for a mobile communication terminal having an idle screen control

function, including the mobile communication terminal on which
desired contents information is displayed through a mobile
communication network; a contents providing server for providing
the contents information; an idle screen providing server that
5 provides a message corresponding to the provided contents
information to a message providing server; and the message
providing server for receiving the message, which is converted
to have an idle screen message format, from the idle screen
providing server, and then providing the message to the mobile
10 communication terminal through the communication network,
wherein the mobile communication terminal comprises a data
viewer, which is a module for receiving push data or pull data
for information set by a user and displaying those data
according to a predetermined format, and the idle screen
15 providing server comprises an idle screen control system that
provides a function of generating an idle screen message, a
contents information management server that provides a community
service, a PDM server that performs an optimization function of
personal information management, and a CRM server that provides
20 a variety of services depending on a user.

According to the system in accordance with the present
invention, the contents information providing server and the
idle screen providing service server can be physically
constructed as a single server. It is also possible to provide
25 information requested by a user using the mobile communication
network for providing relevant information to the mobile

communication terminal according to information that is set by the user who wants to receive the information.

According to the present invention, there is provided a method of controlling and operating resources of an idle screen for a mobile communication terminal in a method of controlling the idle screen of the mobile communication terminal of a system for providing contents information that is transmitted to the mobile communication terminal, including the steps of (a) allowing a user to join a service so as to receive contents information through the mobile communication terminal, and to set or select the contents information; (b) allowing a service server to ~~cooperatively~~ operate cooperatively with a contents information provider, classify multimedia information received from the contents information provider based on the contents information within the service server, and allocate a channel and a stack; (c) allowing idle screen information corresponding to the contents information that is set or selected by the user to be pushed from the service server, and the pushed information to be displayed on an idle screen; (d) allowing the user to pull detailed contents information among pushed contents information on the idle screen, which is displayed on an initial screen, and to receive the pulled contents information; and (e) allowing the contents information that is received in step (d) to be read from a memory and a storage unit of the mobile communication terminal, and the contents information to be displayed according to a predetermined screen configuration of the mobile

communication terminal, wherein the contents information displayed on the idle screen in step (c) is displayed based on a given template configuration.

Advantageous Effects

5 According to a method of the present invention, it is possible to provide information requested by a user using a mobile communication network for providing relevant information to a mobile communication terminal according to information that is set by the user who wants to receive the information. Further,
10 resources stored in a portable mobile communication device, which are frequently used by a user, can be displayed on an idle screen in the form of an icon as a divided screen, a screen of a sliding mode or in explicit real time. Also, a service provider can allocate channels for specific uses such as providing
15 contents and providing a service of an external service provider, and can thus promote various business.

Brief Description of Drawings

FIG. 1 is a view illustrating the configuration of an idle
20 screen service system using a mobile communication network according to the present invention;

FIG. 2 is a diagrammatical view for explaining ~~showing~~ the configuration between a portable mobile communication device and an idle screen control system according to the present

invention;

FIG. 3 is a view of a block diagram showing the construction of an idle screen control server according to the present invention;

5 FIG. 4 is a view of a block diagram showing the construction of a mobile communication terminal according to the present invention;

FIG. 5 is a view ~~for~~ of a flowchart showing~~explaining~~ an idle screen display method of the mobile communication terminal according to the present invention;

10 FIG. 6 is a view of a flowchart ~~for explaining~~showing an information processing structure ~~by the~~ of the service step of the screen display method;

15 FIG. 7 is a view ~~for explaining~~ showing an idle screen template ~~type~~ of the mobile communication terminal according to an embodiment of the present invention;

FIG. 8 is a view ~~for explaining~~ of an idle screen template ~~type~~ of the mobile communication terminal according to another embodiment of the present invention;

20 FIG. 9 is a view ~~for explaining~~showing an idle screen template ~~type~~ of the mobile communication terminal according to still another embodiment of the present invention;

25 FIG. 10 ~~shows~~ is a diagrammatical view showing a channel configuration that is provided from a service provider for providing contents information according to an embodiment of the present invention;

FIG. 11 ~~shows~~ is a diagrammatical view of divided screens
according to an embodiment of channeling of having divided
multimedia screens that are provided in the form of multimedia;

FIG. 12 ~~shows~~ is a diagrammatical view of divided screens
5 according to an embodiment of having divided multimedia screens
that are provided in the form of multimedia;

FIG. 13 is a diagrammatical view ~~for explaining~~ showing a
sliding method, which is an example of an information display
method in which contents information is displayed and an
10 information providing method according to the present invention;

FIG. 14 is a diagrammatical view ~~for explaining~~ showing a
sliding method, which is an example of an information display
method in which contents information is displayed and an
information providing method according to the present invention;
15 and

FIG. 15 is a diagrammatical view ~~for explaining~~ showing an
icon enlargement method, which is an example of an information
display method in which contents information is displayed and an
information providing method according to the present
20 invention. ~~and~~

FIG. 16 is a view ~~for explaining a real-time service~~
~~providing method in the idle screen template type of the mobile~~
~~communication terminal shown in FIG. 9 according to the present~~
~~invention.~~

Best Mode

Preferred embodiments of the The present invention will now be described in detail ~~in connection with preferred embodiments~~ with reference to the accompanying drawings.

5 FIG. 1 is a view illustrating the configuration of an idle screen service system using a mobile communication network according to the present invention.

Referring to FIG. 1, the idle screen service system using the mobile communication network according to the present
10 invention includes a mobile communication terminal 10, an idle screen providing server 20, a mobile communication terminal subscriber information server 30, and ~~a~~an SMS message server 40.

The mobile communication terminal 10 has access to the idle screen providing server 20 through the mobile communication
15 network, sets desired information, receives ~~a~~an SMS message based on the set information through the mobile communication network, stores the received SMS message in a memory of the mobile communication terminal, combines the stored information and converts it into an image form to be displayed, and displays
20 the stored information in a given cycle or when an event occurs.

The idle screen providing server 20 is a server in which a contents providing server for providing a variety of contents and an idle screen providing server are integrated into one. ~~In~~
At this time, the two servers can be physically separated.

25 The contents providing server integrated into the idle screen providing server 20 provides a variety of ~~contents~~

content including news information, financial information, entertainment information, educational information, weather information, shopping information, a schedule, auction information, etc. to the idle screen providing server 20.

5 Further, the contents providing server allows a user to set information that will be received via the mobile communication network in the mobile communication terminal 10, and provides a
an SMS message of contents information, which is converted into an idle screen message format, to the SMS message server 40
10 based on subscription information from the mobile communication terminal subscriber information server 30. ~~In~~At this time, a transmission line of the processed SMS message can preferably include a dedicated line.

The idle screen providing server 20 provides a variety of
15 ~~contents~~content including news information, financial information, entertainment information, educational information, weather information, shopping information, a schedule, auction information, etc. to the mobile communication terminal 10.

The SMS message server 40 receives the SMS message that is
20 processed into the idle screen information form from the idle screen providing server 20, and transmits the SMS message through the mobile communication network.

It has been described above that information of various
25 ~~contents~~content, which has been converted into the idle screen information format, is converted into the SMS message through the SMS message server, which is used in the mobile

communication network, as an example. However, it will be evident that if IMT-2000 and the like including HTTP, CBS, SMS, etc. is commercialized, the above process can be accomplished through a component for converting information into the message
 5 format of IMT 2000.

FIG. 2 is a diagrammatical view for explaining showing the configuration between the portable mobile communication device and the idle screen control system according to the present invention.

10 Referring to FIG. 2, the portable mobile communication device and the idle screen control system according to the present invention includes a data viewer 101, a configuration manager 102, a display manager 103, an event handler 104, a push data manager 105, a pull data manager 106, a data interface
 15 module 107, an administration manager 111, a scheduler 112, a push agent 113, a pull agent 114, a user profile simulator 115, a user profile manager 116, a data format & utility 117, an information match maker 118, a contents server gateway 119 and a database 120.

20 The data viewer 101 includes a module and other utilities that ~~cooperatively operate with an image decode~~ decoder and contents player for allowing information set by a user to be displayed in a format defined by pull data. The configuration manager 102 manages data configuration information of respective
 25 regions constituting the idle screen, and the history that is set by a user through the terminal screen.

The display manager 103 properly displays data constituting the respective regions of the idle screen, and is responsible for the display of text and image, the display of quick launch icons set by a user, a navigation focus process, a pop-up process, and so on. The event handler 104 processes various events generated by a user or a terminal, and is responsible for various key events including a direction key and event processes such as {data view, — and various anti-interruption processes} generated from a terminal. The event handler 104 can execute a built-in browser or a virtual machine (VM) application, etc., if needed.

The push data manager 105 is a module for processing push data, and is responsible for rejection, storage, display, etc. of data. The push data can include control data for initiating a data pull or setting an environment of a terminal, as well as general data. The pull data manager 106 is a module for processing pull data, and can transfer data to the data viewer module for display, if needed. Further, the pull data manager 106 enables a pull operation to be performed according to control data of push data.

The data interface module 107 is constructed utilizing push related API of a terminal, such as SMS, CBS, Data Service, etc., and is responsible for the interface of the idle screen control system.

The administration manager 111 is a module for managing the idle screen control system. It is responsible for management and

authentication of an administrator account, various statistical data reporting, process monitoring and management (start, stop, restart, etc.), configuration and the like. The scheduler 112 allows a user to search a time, cycle, set event, and so on, which are set in a profile, and to perform a necessary operation (push).

The push agent 113 serves to transmit push data that ~~is~~are processed by the data formatter 117 to the push system (SMS, CBS) of the service provider. The pull agent 114 is a module for processing a data pull request from a terminal, and serves to pull data requested by a terminal to the terminal.

The user profile simulator 115 serves to process user profile setting through a PC having access to the Internet and terminal simulation therefore. The user profile manager 116 is a module for allowing a user to manage his profile, and it manages configuration information management of each region, information receive cycle or time setting, change, addition and deletion of a profile, user authentication, and the like, and operates in association with the configuration manager 102.

The data formatter and utility 117 serves to convert data extracted from the information match maker 118 into a format, which can be recognized by the idle screen control client of the terminal before being sent to the terminal. It includes various utilities (image conversion, etc.), which are necessary for data formatting, etc.

The information match maker 118 serves to search data that

is set in a profile by a user and to extract only data set by the user from data received from the contents server.

The contents server gateway 119 is a module that provides an interface for receiving data from an external contents server that provides contents to be transmitted to the terminal. The database 120 serves to store and manage user profile, contents, various statistical information, and the like.

FIG. 3 is a view of a block diagram showing the construction of the idle screen control server according to the present invention.

Referring to FIG. 3, the idle screen control server according to the present invention allows respective functions to provide a wireless Internet push and pull message management solution through optimal cooperation. The idle screen control server includes an idle screen control system 150, a contents management server 151, a PDM server 152, a CRM server 153, an advertising server 154, a pull data controller 155, and so on.

The idle screen control system 150 provides a function of generating an idle screen SMS message, and can perform real-time assignment of channel headers by information, real-time generation and updating of channel information, compression and splitting of image information, and the like. Further, the contents management server 151 can provide information such as news, finance, entertainment, fortune and shopping, positional information, community service of meeting information, etc. The PDM server 152 allows management of personal information to be

optimized. In addition, the CRM server 153 allows a variety of services based on a user's propensity to be easily provided. The advertising server 154 is responsible for various banner advertising, policy public information, etc. through an a wireless Internet connection.

The pull data controller 155 manages updating of information when an event occurs or at a given cycle in response to an information transmission module, which is requested by a portable mobile communication device. It also transmits data according to a request from the terminal, and allows synchronization of personal information between the terminal and the server.

FIG. 4 is a block diagram showing the construction of a mobile communication terminal according to the present invention.

An owner of a mobile communication terminal can specify the type of an information service, which will be provided through a screen of the terminal, and the type that the service is displayed on the screen.

The terminal must display IOD (Information On Demand) provided by the server in the form desired by a user. The terminal processes a request for IOD information through two types.

The first type is to process SMS message information or location or environment information for requesting a server for information through push data. The received SMS information is managed by the storage of the terminal. If the push data have

SMS information to be displayed on the screen, they are displayed through an IntroPAD UI manager 410. If the push data are environment information related to display environment or information cycle, they are processed by an IntroPAD configurator 420. The IntroPAD configurator 420 processes information on an updating cycle or a display type through the scheduler 430 and the IntroPAD UI manager 410.

The second type is a process depending on the updating cycle. That is, the scheduler 430 requests the IOD data from the server to a pull handler 44 every updating cycle that is specified by a user. The pull handler 440 receives pull data from a pull server (not shown) and stores the pull data in a storage region of the IntroPAD pull data 450, and transfers the received information to the IntroPAD UI manager 410 so that it is displayed on the mobile communication terminal of the user.

FIG. 5 is a view of a flowchart showing~~for explaining~~ an idle screen display method of the mobile communication terminal according to the present invention.

A user joins a service in order to receive ~~contents~~content information using a mobile communication terminal, and sets or selects the contents information (S501). The service-providing server can cooperatively operate with the contents information provider, and can include the contents providing server. The service-providing server serves to classify text information according to ~~contents~~content information within the server, and allocates a stack (S502).

An idle screen corresponding to the contents information, which is set or selected by the user, is pushed from the service-providing server. The pushed information is displayed on the idle screen (S503). ~~In~~At this time, the method further includes the steps of, before the pushed information is displayed on the idle screen, determining whether a SMS message has been received, and if it is determined that the SMS message is received, determining whether a corresponding SMS message is idle screen information,~~;~~if it is determined that the received SMS message is a common SMS message, displaying the common SMS message on the display unit (S504~~;~~;); and if the received SMS message is idle screen information, classifying an idle screen message and then storing the classified messages in a given stack of the memory.

~~In~~At this time, the received idle screen message can be set ~~in~~to a mode in which a specific ~~contents~~content is set if the user of the mobile communication terminal wants to receive it, or can be provided in a mode of pushing given information for advertising on the part of a contents provider.

Then, a user can pull detailed ~~contents~~content information from among the push ~~contents~~content information from the idle screen displayed on the initial screen, and then receive the requested ~~contents~~content information (S505). The ~~contents~~content information received at step S505 is read from the memory and the storage unit of the mobile communication terminal, and is displayed according to a predetermined screen

configuration of the mobile communication terminal (S506).

Thereafter, the ~~contents~~content information displayed on the idle screen at step S503 is displayed according to a given template configuration.

FIG. 6 is a view of a flowchart for explaining an information processing structure by the service step.

Referring to FIG. 6, in a service-providing server 600, an information type 601 can be configured according to a ~~contents~~content type 603, and a channel configuration 602 can be constructed according to the ~~contents~~content type 603. In a mobile communication terminal 610, a template type 604 can be constructed according to the ~~contents~~content type, and a display mode 605 can be ~~decided~~determined and displayed.

The ~~contents~~content type 603 is a classification system depending on a ~~contents~~content type that is provided to a ~~contents~~content provider (CP). The ~~contents~~content type is classified into text, image, animated image, motion picture, table and so on, which are respectively defined to be C1, C2, C3, C4, C5, C6, etc. The platform supports file formats such as .txt, .bmp, .png, .Gif, .sis, and .mpeg according to the ~~contents~~content type. The size of data is classified as push and pull information, and is defined according to the ~~contents~~content type.

The configuration of the information type 601 depending on the ~~contents~~content type is classified into a push information type and a pull information type. The push information is

classified into Notification type and Information type. Notification type has only a call back address value for data pull, and Information type has some information and a call back address value and supports SMS Push, Wap push, http push.

5 Information type can support detailed information in the case of http push. Pull information is classified into Push & Pull type and Find & Pull type. Push & Pull type is for retrieving detailed information through Call back of Information push or Notification push. Find & Pull type is for retrieving detailed
10 information of corresponding data.

The channel configuration 602 is provided according to a template that provides information classified by every ~~contents~~ content type. The template type 604 is divided into Main, Sub, and others depending on UI. The display mode 605 provides a
15 sliding method, an icon enlargement method, a channel switch method, or an explicit real-time mode method. The channel configuration 602, the template type 604 and the display mode 605 will be described in detail later on.

FIG. 7 is a view ~~for explaining~~ showing an idle screen
20 template ~~type~~ of the mobile communication terminal according to an embodiment of the present invention.

Referring to FIG. 7, a region 701 is a region for displaying up to 4 services in the form of multimedia, and providing various display modes so that various display layouts
25 can be provided to a user. A region 702 is a region for displaying a quick launch icon for executing resources within a

portable mobile communication device or a VM application and having access to a wireless Internet web site in a small icon form.

FIG. 8 is a view ~~for explaining~~showing an idle screen template ~~type~~ of the mobile communication terminal according to another embodiment of the present invention.

Referring to FIG. 8, a region 801 is a region for displaying sliding text and sliding images. A region 802 is a region for displaying up to four services in ~~the~~multimedia form ~~of multimedia~~. A region 803 is a region for displaying a quick launch icon for executing resources within a portable mobile communication device or a VM application and having access to a wireless Internet web site in a small icon form.

FIG. 9 is a view ~~for explaining still~~showing an idle screen template ~~type~~ of the mobile communication terminal according to still another embodiment of the present invention.

Referring to FIG. 9, a region 901 is a region for displaying a title bar to represent the type of an idle screen service. A region 902 is a channel switch region for changing the content display ~~of contents~~. A region 903 is a region for displaying a ~~contents~~content information service in ~~the multimedia form of multimedia~~. A region 904 shows a quick launch icon for executing resources within a portable mobile communication device or a VM application and having access to a wireless Internet web site in a small icon form, and a real-time information providing icon capable of receiving information in

real time.

FIG. 10 shows a channel configuration that is provided from the service provider for providing ~~contents~~content information according to an embodiment of the present invention. There is shown in FIG. 10 an embodiment in ~~the~~a case where ~~contents~~content information is pushed to the mobile communication terminal. However, even when detailed information on ~~contents~~content information is pulled, a channel configuration is possible. It is possible to construct a channel by classifying a sliding region 1010 and an image region 1020 among a divided screen displayed on the mobile communication terminal. Further, the sliding region 1010 is composed of a text information channel 1010a that contains only text information and an image information channel 1010b that contains image information. The image region 1020 on which the contents information is displayed is composed of a channel 1020a in which text and image contain mixed information.

~~In~~At this time, types C1 to C6 of the ~~contents~~content information, which correspond to respective channels of each of the regions, are specified. The channel configuration on the service provider side is connected to the screen region of the mobile communication terminal. A concrete example of the channel configuration displayed on the screen of the mobile communication terminal is shown in FIG. 11.

FIG. 11 shows an embodiment of the template configuration displayed on the display of the mobile communication terminal

when the divided screen provided in ~~the multimedia~~ form of ~~multimedia~~ is channeled. As shown in FIG. 11, regions that display the multimedia screen shown in FIGS. 7 to 9 can be channeled for every contents-content information type. Further, the screen, which is displayed when the channel constructed by the ~~contents-content~~ information providing server shown in FIG. 10 is displayed on the mobile communication terminal associated therewith, can ~~be~~ have various displays ~~displayed variously~~ depending on the template configuration shown in FIG. 11.

~~In~~ At this time, a user can select a corresponding channel, enlarge ~~contents-content~~ information that matches the corresponding channel, and display the enlarged ~~contents-content~~ information.

FIG. 12 shows divided screens according to an embodiment ~~having of~~ divided screens that are provided in ~~the multimedia form of multimedia~~. As shown in FIG. 12, if corresponding contents information is selected and displayed in the region where the multimedia screen shown in FIGS. 7 to 9 is displayed, only text can be displayed (1201), only image and text or image can be displayed (1202), information can be tabled and displayed (1203), and text information can be listed and displayed (1204).

FIGS. 13 and 14 ~~is~~ are diagrammatical views showing view ~~for explaining~~ a sliding method, which is an example of an information display method, in which ~~contents-content~~ information is displayed, and an information providing method according to the present invention.

Referring to FIG. 13, if sliding text information 1301 is confirmed or a service call key is selected, a message indicating that detailed information is called is displayed on the screen window of the mobile communication terminal (1302).

5 Detailed information corresponding to the selected information is then displayed (1303). Further, referring to FIG. 14, if sliding image information 1401 is confirmed or a service call key is selected, a message indicating that detailed information is called is displayed on a screen window of a mobile
10 communication terminal (1402). Detailed information (image and text information) corresponding to the selected information is then displayed (1403). ~~In~~ At this time, the display presented in 1302 and 1402 can be omitted.

FIG. 15 is a diagrammatical view ~~for explaining~~ showing an
15 icon enlargement method, which is an example of an information display method in which ~~contents~~ content information is displayed and an information providing method according to the present invention.

Referring to FIG. 15, if ~~contents~~ content information is
20 selected from an image region 1501 that is divided and displayed in the multimedia form ~~of multimedia~~ by using an enlargement icon, a corresponding image is enlarged and displayed. ~~In~~ At this time, it is possible to enlarge a corresponding image in the image region 1501 when it is activated using an up and down
25 key or selected using a select key. If a confirmation or service call key is selected from an enlarged image region 1502, a

message indicating that an idle screen message is called is displayed on the screen window of the mobile communication terminal (1503). Detailed information corresponding to the selected information is displayed (1504).

5 ~~FIG. 16 is a view for explaining a real-time service providing method in the idle screen template type of the mobile communication terminal shown in FIG. 9 according to the present invention.~~

10 ~~Referring to FIG. 16, if a channel is selected in the region 902 of FIG. 9 to select a real-time icon 1601 of the mobile communication terminal, the function is operated in real time to provide information. If the real-time icon 1601 is selected, the operation of the real-time function is released. Contents that will be provided in real time can include contents~~
15 ~~that change in real time, such as a current price, a current price of securities issue, chart and stock price index. In this time, in the real-time information providing method, information can be received only an instant time desired by a user so that information by explicit selection of the user can be provided.~~
20 ~~It is thus possible to provide means that can prevent unnecessary information from being provided and can provide information of a high quality to a user.~~

Industrial Applicability

25 According to the present invention, in order to provide useful information to a user, the information is stored in the

user's mobile communication terminal and the stored information can be displayed periodically or when an event occurs. Thus, a load of~~an~~on the information provider system can be removed.

Further, a user can consistently confirm the use of received idle screen information consistently or when an event occurs. It is thus possible to maximize efficient use ~~efficiency~~ of information.

Also, a user can set not only specialized information such as financial information and entertainment information, but also a variety of contents provided by a contents provider system using a portable mobile communication device. Thus, the type of received information can be diversified and can be used usefully in a Push & Pull mode.

Moreover, more detailed information can be provided through interactive settings through access with a related wireless Internet web site by means of a hyperlink function for receiving the information corresponding to information provided.

Further, an operator of a mobile communication network can perform advertising and campaigns for various advertising services, public notices, etc. for every customer. Thus, ~~a~~-user-friendly management is possible.

Furthermore, internal resources that are frequently used by a user are disposed in an idle screen of a portable mobile communication device. It is thus possible to operate a user-oriented terminal.

In addition, some of the channels that are constructed as

means for providing information can be transferred and leased to
an external service provider. It is thus possible to ~~service~~
provide a variety of ~~contents~~ content and information. This
reduces ~~overlapped~~ overlapping developments ~~of~~ in a service
5 infrastructure and allows mobile communication resources to be
more efficiently utilized and operated.